

Gauge	5/32	
Manufacturing	Twist	
Pile description	Velluto	
Primary backing	Woven	
Pile weight	1000 gr/m <sup>2</sup>	
Number of tufts	80.600/m <sup>2</sup>	
Secondary backing	Premiumback	Actionback
Width	400/500 cm	400/500 cm
Total weight	1775 gr/m <sup>2</sup>	1750 gr/m <sup>2</sup>
Total height	9,6 mm	8,6 mm
Pile In/Out	Out	In
Roll length	25 m	25 m
DOP	1087#219006/EXE/H	1087#219006/EXE/SSB
Fire classification	Efl	Efl
Use classification	22	22
TOG rating	1,4	1,3



Available colours	Premiumback   400/500 cm	109   131   141   155   161   222   240   305   335   407   437   511   893   897
	Actionback   400/500 cm	109   131   141   155   161   222   240   305   335   407   437   511   893   897

Colour legend	109	Steel	131	Castlerock	141	Black
	155	Pigeon	161	Charcoal	222	Everglade
	240	Pine	305	Pearl	335	Cappuccino
	407	Lavender Stone	437	Cranberry	511	Curry
	893	Denim	897	Midnight Blue		

7E3B8BC0

www.pro-dis.info

EN 14041

DOP: 1087#219006/EXE/H

B.I.G. Floorcoverings nv  
Rijksweg 442  
B - 8710 Wielsbeke

For use as floor covering in buildings.

EMISSIONS DANS L'AIR INTÉRIEUR

These details are approximate. Complete specification details and associated certificates together with tolerances applying to the above can be provided upon request. We reserve the right to modify technical specifications without prior notice. Due to method of manufacture perfect pattern and/or colour matching can not be guaranteed. In cut-pile carpeting, in rare cases, shading/pile reversal may occur without affecting its fitness for use. Shading/pile reversal can not be considered as a manufacturing or a material defect and will not affect the durability of the carpet.







109 - 400/500 cm



131 - 400/500 cm



141 - 400/500 cm



155 - 400/500 cm



161 - 400/500 cm



222 - 400/500 cm



240 - 400/500 cm



305 - 400/500 cm



335 - 400/500 cm




407 - 400/500 cm



437 - 400/500 cm



511 - 400/500 cm



893 - 400/500 cm



897 - 400/500 cm