




PRODUCT SPECIFICATION					DATE: 27/02/09
PRODUCTNAME: COMMERCIAL : Atlas gel PRODUCTION : Hercules QC res.gel CODE : 976 . . . 010 062					 EN 14041  
COLOURS/FARBEN 1861;2862;2868;3879;5865;5880;6883; COLORIS/KLEUREN:					
WIDTH/BREITE/LARGEUR/BREEDTE: 1 m 2 m 4 m LENGTH/LÄNGE/LONGUEUR/LENGTE: 25 m 25 m 25 m					
REMARKS/BEMERKUNGEN/REMARQUES/OPMERKINGEN: 4m: min. order qty = 1 standard unit 2m: min. order qty = 1 standard unit 1m: min. order qty = 100 m ² /colour					
TECHN. INFORM.	TECHN. DATEN	CAR.TECHN.	TECHN. GEGEV.	NORM	
MANUFACTURING PROCESS	HERSTELLUNGS-ART	TECHN. DE FABRICATION	FABRICATION-METHODE	DIN61151	needle-felt
SURFACE ASPECT	OBERFLÄCHEN-STRUKT.	ASPECT DU SURFACE	POOL-STRUCTUUR		ribbed
PILE COMPOSITION	POL MATERIAL	COMP. DU POIL	POOL-MATERIAAL		100% Polyprop.
PILE WEIGHT	POLGEWICHT	POIDS DU POIL	POOLGEWICHT	ISO8543	790gr/m ² ± 10%
PILE HEIGHT	POLHÖHE	HAUT. DU POIL	POOLHOOGTE		4mm ± 10%
PRIM. BACKING	PRIM. RÜCKEN-AUSSTATTUNG	DOSSIER PRIM.	PRIM. BACKING	ISO2424	Carboxylated styrene butadiene latex
SEC. BACKING	SEC. RÜCKEN-AUSSTATTUNG	DOSSIER SEC.	SEC. BACKING	ISO2424	gel foam
BACKING WEIGHT	RÜCKEN-GEWICHT	POIDS DU SUPPORT	BACKING-GEWICHT		585gr/m ² ± 10%
TOTAL WEIGHT	GESAMTGEWICHT	POIDS TOTAL	TOTAALGEWICHT	ISO8543	1375gr/m ² ± 10%
TOTAL HEIGHT	GESAMTHÖHE	HAUTEUR TOT.	TOT. HOOGTE	ISO1765	7mm ± 10%
TECHN. INFORM.	TECHN. DATEN	CAR.TECHN.	TECHN. GEGEV.	NORM	
PERMANENT ANTISTATIC	PERMANENT ANTISTATISCH	ANTISTATIQUE PERMANENT	PERMANENT ANTISTATISCH	ISO6356	
TO/RUBBING	REIBECHTHEIT	AU FROTTEM.	WRIJFECHTH.	ISO105X12	4 Except For 3879 3
CLASSIFICATION	KLASSIFIKATION	CLASSIFICATION	CLASSIFICATIE		
FLAMMABILITY	BRAND-VERHALTEN	COMPORTEMENT AU FEU	BRANDGEDRAG	EN 13501-1	Efl - fully adhesive
USAGE	ANWENDUNG	EMPLOI	GEBRUIK		domestic
Due to limitations of the manufacturing process, colour may slightly vary from batch to batch. We reserve the right to alter technical specifications.	Durch dem Produktions Prozess bedingt, können geringe Farbabweichungen von Partie zu Partie auftreten. Wir behalten uns das Recht um die Technischen Daten zu ändern.	Du à des limitations de production, le coloris peut varier légèrement d'une production à l'autre. Le fabrication se réserve le droit de modifier les caractéristiques techniques.	Door beperkingen in het productieproces, zijn geringe kleurafwijkingen van partij tot partij mogelijk. Wij behouden het recht de technische gegevens aan te passen.		