


Version: 11/2023



vinyl planks & tiles.

Rigid click	Contains	m ²	Gross Weight
1 pack regular planks ZENN	8 planks	1,73 m ²	17,78 kg
1 pallet regular planks ZENN (incl. pallet)	45 packs	78,04 m ²	830,10 kg
1 pack tiles ZENN	4 tiles	1,67 m ²	17,18 kg
1 pallet tiles ZENN (incl. pallet)	50 packs	83,61 m ²	889 kg
1 pack Herringbone planks ZENN	30 planks	1,97 m ²	19,70 kg
1 pallet Herringbone planks ZENN (incl. pallet)	40 packs	78,96 m ²	842 kg

Product specifications	Norm	Rigid click vinyl planks & tiles		
		Regular plank	Herringbone plank	Tile
Dimensions		L 1219,2 x W 177,8 mm	L 609,6 x W 107,95 mm	L 914,4 x W 457,2 mm
Integrated underlay		5 + 1 mm	5 + 1 mm	5 + 1 mm
Total thickness	EN ISO 24346	6 mm	6 mm	6 mm
Thickness of the wear layer	EN ISO 24340	0,55 mm	0,55 mm	0,55 mm
Locking system				
Usage classification	EN ISO 10874	23/33	23/33	23/33
Commercial warranty		10 years	10 years	10 years
Residential warranty		Lifetime	Lifetime	Lifetime

Test results		
Underfloor heating	EN ISO 12524	suitable max. 27° (80°F) / electrical floor heating systems: max 60 W/m ²
Castor chair	EN ISO 4918	pass
Fire resistance	EN ISO 13501-1	Bfl-s1
Chemical resistance	EN ISO 26987	OK
Residual indentation	EN ISO 24343-1	≤ 0,1mm
Thermal resistance	EN ISO 8302	0,030 m ² K/W
	DIN 51130	R10
Slip resistance	EN ISO 13983	class DS
Sound reduction: impact sound	EN ISO 717-2	19 dB
Dimensional stability	EN ISO 23999	< 0,15 % - pass
Lock Strength	EN ISO 10582	> 1,5 kN/m - pass

