

Mustang tiles

Tuft gauge	1/10 loop pile	ISO 2424
Pilecomposition	100% PA SDN	ISO 2424
Primary Backing	Non Woven	ISO 2424
Secondary backing	Bitumen	ISO 2424
Width	50 x 50 cm ± 0,2%	EN 986
Pile Density	0,139 gr/cm ³	ISO 8543
Pile Weight	550 gr/m ²	ISO 8543
Total weight	4300 gr/m ² ± 15%	ISO 8543
Pile height	3 mm	ISO 1765
Total Height	5 mm	ISO 1765
Number of knots	189.600/m ² -7.5% .+10%	ISO 1763
Fire Classification	Bfl-S1	EN 13501-1
Use Area	Heavy project use (33)	EN 1307
GUT Nr.	F7FCFD0C GUT	www.pro-dis.info
Evaluated sound absorptions grade αW	Ca. 0,15 αW	ISO 11654
Sound Insulation	Ca. 25 dB	ISO 10140
Thermal resistance	Ca. 0,07 M ² KW	ISO 8302
Light fastness	≥ 5	105-B02
Wearebility	≥ 4	105-X12
Water fastness	≥ 4	105-E01
Electrostatic charging	<2 kV	ISO 6356
Luxury class	LC2	EN 1307
Pictures	www.condorcontract.com	

Floorsymbols



Certificates

