

Preston GC

Manufacturing process	Tufted	ISO 2424
Gauge	1/8" Cutpile	
Fibre composition	100% PP	
Primary backing	Woven	
Backing	GC	ISO 2424
Total fibre weight of use surface	250 gr/m ²	
Total weight	810 gr/m ²	+/- 15% ISO 8543
Pile height	4,0 mm	ISO 1766
Total height	7,0 mm	+15% / -10% ISO 1765
Tufts per 10cm	27	
Tufts per m²	86000	
Colour fastness to light	> 7	ISO 105-B02
Roll width	100 cm, 133 cm, 200 cm, 300 cm, 400 cm	EN 984
Application	Landscaping	

Floorsymbols



ISO 9001:2015-certified processes
 ISO 14001:2015-certified processes

2022-01-26

Vebe Floorcoverings b.v. products are to be installed in full accordance with Vebe installation instructions and recognised trade standards. An effective, regular cleaning and maintenance programme is vital for retaining a high appearance level. Vebe products should only be used as floorcoverings. Note: Vebe Floorcoverings b.v. reserves the right to adapt this specification without giving prior notice. For the latest versions of the technical specifications, check our internet site.

In the area of office chairs we recommend to use mats made of polycarbonate. This extends the life of your carpet.

During normal use, maintenance and cleaning procedures, the mentioned products will be guaranteed for a period of 2 years on the carpet-properties and UV-resistance.

Due to sunshine (UV-radiation) and / or moisture the color of the fibers will change in time. This is usual for the mentioned products.

With artificial grass, weather conditions may cause a shrinkage of $\pm 2\%$.