

# Vienna

## Technical Specifications

Manufacturing method	: Level loop
Pile type	: Loop pile
Pile fibre	: 100% polypropylene solution-dyed
Gauge	: 1/10"
Pile weight	: 400 gr/m <sup>2</sup>
Pile height	: 2.9 mm
Total weight	: 3700 gr/m <sup>2</sup>
Total thickness	: 4.4 mm
Tuft density	: 193.550/m <sup>2</sup>
Tile size	: 400 cm
Backing	: Actionback



Odkryj więcej!

made with  
**select** yarns®

## Performance

Use classification	: 31
Caster chair test	EN 985 : B, occasional use
Abrasion	EN 1963 : Pass
Vettermann test	EN 1471 : Pass
Dimensional stability	EN 986 : Pass
Thermal isolation	ISO 8302 : 0.10 m <sup>2</sup> K/W
Luxury class	: LC1
DOP-nr	: 1016-3012

## Electrostatic


Static loading	: Anti-static
----------------	---------------

## Flammability

Reaction to fire EN ISO 9239-1	: Cfl-s1
Reaction to fire BS 4790	: Low radius of effect of ignition

## Colour fastness

Light	ISO 105 B02	: 7.0 – 8.0
Rubbing	ISO 105 x12	: 4.5



## Maintenance

Regular vacuum cleaning is essential. Spills and surface stains can be removed by sponging with a damp cloth, or for more resistant stains, with a mild detergent solution.



Betap has the right to alter each product specification in order to improve the carpet according to the newest technological applications.

  
**betap**®  
Flooring since 1918