

## Structura

<b>Tuft gauge</b>	1/10 cut pile	ISO 2424
<b>Pilecomposition</b>	100% PP	ISO 2424
<b>Primary Backing</b>	Non Woven	ISO 2424
<b>Secondary backing</b>	Felt	ISO 2424
<b>Width</b>	400 cm ± 1%	EN 984
<b>Pile Weight</b>	800 gr/m <sup>2</sup>	ISO 8543
<b>Total weight</b>	Felt : 1800 gr/m <sup>2</sup> ± 15%	ISO 8543
<b>Pile height</b>	5 mm ± 2 mm	ISO 1766
<b>Total Height</b>	Felt : 8 mm	ISO 1765
<b>Number of knots</b>	237000 /m <sup>2</sup> -7.5% .+10%	ISO 1763
<b>Fire Classification</b>	Efl	EN 13501-1
<b>Use Area</b>	Heavy domestic use (23)	EN 1307
<b>Light fastness</b>	≥5	105-B02
<b>Wearebility</b>	≥4	105-X12
<b>Water fastness</b>	≥4	105-E01

## Floorsymbols



## Certificates



2024

Condor Carpets  
Euroweg 3  
8061 SB Hasselt

EN1307

DOP: C-027FG009

Reaction to fire:  
Cl-s1  
I658

Slip resistance: DS

AB

Resilient floor  
covering to be  
used within a  
building