

FLAMINGO

Manufacturing process	Tufted	ISO 2424
Gauge	5/32" Loop	
Pilecomposition	100% PP	ISO 2424
Primary backing	Woven PP	ISO 2424
Secondary backing	AB + Felt	ISO 2424
Width	400 cm, 500 cm	± 1% EN 986
Pile weight	approx. 600 gr/m ²	ISO 8543
Total weight	AB : approx. 1718 gr/m ² Felt : approx. 1760 gr/m ²	± 15% ISO 8543
Pile height	approx. 5,0 mm	ISO 1765
Total height	AB : approx. 6,0 mm Felt : approx. 7,0 mm	+ 15% / -10% ISO 1765
Number of knots	approx. 75.825 /m ²	+ 10% / -7,5% ISO 1763
Fire classification	AB : Efl Felt : Efl	EN 13501-1
Light fastness	≥ 5	105-B02
Wearability	≥ 4	105-X12
Water fastness	≥ 4	105-E01
Thermal resistance	0,130 m ² K/W	ISO 8302
Sound insulation	20,0 dB	ISO 10140
GUT Nr.	AB : DBDCFEC7 Felt : 7F62A7A7	

Floorsymbols



Certificates

<p>EN 14041 19</p>  <p>Reaction to fire: Efl</p> <p>Slip resistance: DS AB DOP: 1058-126373</p> <p>Textile Floorcovering EN1307</p>	<p>EN 14041 18</p>  <p>Reaction to fire: Efl</p> <p>Slip resistance: DS Felt DOP: 1058-126111</p> <p>Textile Floorcovering EN1307</p>				
--	--	---	---	---	---