


Eternity-Special

Tuft gauge	5/32 cut pile	ISO 2424
Pilecomposition	100% PES	ISO 2424
Primary Backing	Woven	ISO 2424
Secondary backing	Felt	ISO 2424
Width	400 cm ± 1%	EN 984
Pile Weight	1150 gr/m ²	ISO 8543
Total weight	Felt : 2150 gr/m ² ± 15%	ISO 8543
Pile height	14 mm ± 2 mm	ISO 1766
Total Height	Felt : 17 mm	ISO 1765
Number of knots	80000 /m ² -7.5% .+10%	ISO 1763
Fire Classification	Cfl-S1	EN 13501-1
Use Area	Heavy domestic use (23)	EN 1307
Light fastness	≥ 5	105-B02
Wearebility	≥ 4	105-X12
Water fastness	≥ 4	105-E01

Floorsymbols



Certificates

 2024 Condor Carpets Euroweg 3 8061 SB Hasselt EN1307 DOP: C-025FE266 Reaction to fire: Cfl-s1 1658 Slip resistance: DS Felt Resilient floor covering to be used within a building	 2024 Condor Carpets Euroweg 3 8061 SB Hasselt EN1307 DOP: C-025FE266-UK Reaction to fire: Cfl-s1 1658 Slip resistance: DS Felt Resilient floor covering to be used within a building	 www.blauer-engel.de/uz128	 eurofins GOLD CERTIFIED PRODUCT	 A+ A B C	 TÜV PROFI CERT product 70 710 6845-2 www.profi-cert.com TFI tested for emissions, harmful substances PREMIUM
---	--	-------------------------------	---	--------------	--