

## Croatia

<b>Tuft gauge</b>	1/8 cut pile	ISO 2424
<b>Pilecomposition</b>	100% PP	ISO 2424
<b>Primary Backing</b>	Woven	ISO 2424
<b>Secondary backing</b>	Felt	ISO 2424
<b>Width</b>	400 cm ± 1%	EN 984
<b>Pile Weight</b>	650 gr/m <sup>2</sup>	ISO 8543
<b>Total weight</b>	Felt : 1550 gr/m <sup>2</sup> ± 15%	ISO 8543
<b>Pile height</b>	10 mm ± 2 mm	ISO 1766
<b>Total Height</b>	Felt : 13 mm	ISO 1765
<b>Number of knots</b>	70875 /m <sup>2</sup> -7.5% .+10%	ISO 1763
<b>Fire Classification</b>	Efl	EN 13501-1
<b>Use Area</b>	Medium domestic use (22)	EN 1307
<b>Light fastness</b>	≥5	105-B02
<b>Wearebility</b>	≥4	105-X12
<b>Water fastness</b>	≥4	105-E01

## Floorsymbols



## Certificates



Condor Carpets  
 Euroweg 3  
 8061 SB Hasselt  
 EN1307  
 DOP: C-001FC304  
 Reaction to fire:  
 Efl  
 Slip resistance: DS  
 Felt  
 Resilient floor  
 covering to be  
 used within a  
 building



Condor Carpets  
 Euroweg 3  
 8061 SB Hasselt  
 EN1307  
 DOP: C-001FC304-UK  
 Reaction to fire:  
 Efl  
 Slip resistance: DS  
 Felt  
 Resilient floor  
 covering to be  
 used within a  
 building



www.blauer-engel.de/uz128

