

Goodwood

Tuft gauge	1/8 cut pile		ISO 2424
Pilecomposition	100% PP		ISO 2424
Primary Backing	Woven		ISO 2424
Secondary backing	Felt		ISO 2424
Width	400 cm, 500 cm	± 1%	EN 984
Pile Weight	720 gr/m ²		ISO 8543
Total weight	Felt : 1720 gr/m ²	± 15%	ISO 8543
Pile height	8 mm	± 2 mm	ISO 1766
Total Height	Felt : 11 mm		ISO 1765
Fire Classification	Efl		EN 13501-1
Use Area	Medium domestic use (22)		EN 1307
Light fastness	≥ 5		105-B02
Wearebility	≥ 4		105-X12
Water fastness	≥ 4		105-E01

Floorsymbols



Certificates

 Condor Carpets Euroweg 3 8061 SB Hasselt EN1307 DOP: C-001FG026 Reaction to fire: Efl Slip resistance: DS Resilient floor covering to be used within a building	 Condor Carpets Euroweg 3 8061 SB Hasselt EN1307 DOP: C-001FG026-UK Reaction to fire: Efl Slip resistance: DS Resilient floor covering to be used within a building	 www.blauer-engel.de/uz128	 eurofins GOLD CERTIFIED PRODUCT	 A+ A B C	 70 710 6845-1 www.profitcert.com tested for emissions, harmful substances PREMIUM
--	---	--	---	--------------	--